

FLEXIBLE MAGNETIC MATERIALS | SPECIFICATION OF DM-8 ADHESIVE

ISO 9001 and ISO 14001 Certified
Version 1.0

Mold:	DM-8#
Base material:	MYLAR, 0.025MM thickness
Release paper:	red release film
Color:	red
Application:	Suitable for furniture, window and other articles' mounting
Product characters:	good initial adhesion, adhesion and temperature resistance, anti-UV and high transparent MYLAR
Temperature range:	-10°C~90°C

TECHNICAL DATA

Adhesive:	0.095mm~0.100mm
Total thickness:	0.215~0.225mm
Shear adhesion:	>24 hrs (1kg/2.5cm×2.5cm)
Initial adhesion:	> 5cm
Adhesion:	>2500 g/2.5cm or 24.4N/2.5cm

Remark:

- (1) Test temperature: 23+/-2°C and humidity degree 60% RH +/-5% RH
- (2) Storage environment 20°C~30°C, avoid high-humidity environment!
- (3) Storage life: 1 year

IMPORTANT NOTICE

Published information concerning Bakker Magnetics products is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of Bakker Magnetics products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice. Bakker Magnetics 2015.